


## **BUFFALO ROAD BLOCKER**





Buffalo Series Road Blocker is designed for long life operation specially to provide passing safety and control..

Durability of product has proven by the crash test which realized with 7 tonnes vehicle incoming 88 kmh speed.

Standard production length is variable from 2 M to 6 M, and movable part height can be change from 50 CM to 100 CM.

Buffalo series road blocker designed and produced as fully compliant for all kind of access control systems..

Road blocker main structure has built from S235JR quality steels, all hydraulic parts like unit, valves, locks are from BOSCH - Rexroth brand.

#### General Informations and Standards

- TMAG Control Card
- 2-3 M single piston, 4-5-6 M double piston
- 4-6 sec operation speed
- 3/8R2 Hydraulic hoses 330 bar withstand
- Crash test certificated
- 100% heavy duty cycle
- Fully compliant for access control systems
- Safety Photocell and support
- WR100 Desktop button system
- High performance working
- Fully safe and reliable operation
- Remote control and receiver system
- 2 years warranty
















# TECHNICAL SPECIFICATIONS


#### **Product Details**





#### **Dimensions**





													LE	ENGT	H											
				2 M					3 M					4 M					5 M					6 M		
		Α	В	С	D	Е	Α	В	С	D	Е	Α	В	С	D	Е	Α	В	С	D	Е	Α	В	С	D	Е
	50 cm		945	730	500			945	730	500			945	730	500			945	730	500			945	730	500	
N.G	60 cm	1	1045	850	600			1045	850	600		4000	1045	850	600			1045	850	600	00	6000	1045	850	600	6030
	70 cm		1145	950	700			1145	950	700			1145	950	700			1145	950	700			1145	950	700	
	80 cm		1245	1050	800		3000	1245	1050					1050		4030 5		1245	1050					1050		
RISI	90 cm	2000	1345	1150	900	2030	3000	1345	1150	900	3030	4000	1345	1150	900	4030	3000	1345	1150	900	15030	10000	1345	1150	900	6030
12	100 cm		1445	1250	1000			1445	1250	1000			1445	1250	1000			1445	1250	1000			1445	1250	1000	.]
	110 cm		1545	1350	1100			1545	1350	1100			1545	1350	1100			1545	1350	1100			1545	1350	1100	
	120 cm		1645	1450	1200			1645	1450	1200			1645	1450	1200			1645	1450	1200			1645	1450	1200	



### **TECHNICAL SPECIFICATIONS**

Forceful Series Road Blocker destroyed the 7000 kg truck, which is incoming 88 kmh speed, as completely unusable state and didn't allow passing, therefore it has proved 100% Safety by the K12 crash test certification.













### **Technical Datasheet**

Туре	BUFFALO SERIES									
Model	WBF200	WBF300	WBF400	WBF500	WBF600					
Length	2 mt	3 mt	4 mt	5 mt	6 mt					
Movable Part	S235JR quality sheet – Upper sheet 10mm / Front sheet 4mm / Side sheet 4mm / Inner enforcements 4mm									
Working System	Hydraulic									
Power Supply	380 V 3 Phases 50/60 Hz									
Control Card	T-MAG Control Card									
Current	3,8	Α		5,15 A						
Motor Power	1,5	KW	2,2 KW							
IP Standard			54							
Number of piston	Single	Piston		Double Pistons						
Opening Time	4-6 sec									
Duty Cycle	100%									
Lift power	900 Kg 1800 Kg									
Limit Switch Type		Adjusta	able engine working	period						
Working Pressure Min			20 Bar							
Working Pressure Max			75 Bar							
Manual Opening			None							
Manual Closing		C	Optional Handle Pun	пр						
Hydraulic Oil Type		32 or	46 number hydraul	ic oil						
Warning Light	Power Solar Red Led assembled on side ironsheets									
Hydraulic Hose	3/8 R2 330 Bar									
Working Temperature	-20°C min +70°C max									
Accumulator Supply	None									
Emergency Close			Optional							
Water Drainage Pump			Optional							
Crash Test			Test Certificate							

#### Optional Extras

Oil Heater

Oil Cooler

- PLC Control Panel
- PLC Control Screen
- **Emergency Fast** Operation (1 sec)
- Manual Hand Pump
- Traffic Lights (red-green)
- Traffic Lights Post
- Automatic Water Pump
- Loop Dedector
- **Checkered Plate**
- Hot Dip Galvanization

#### **ADRESS**

Organize Sanayi Bölgesi 9. Cad. No. 1 KARAMAN, TR

T: 0 338 224 13 60

F: 0 338 224 14 46

M: whiterose@whiterose.com.tr

W: www.whiterose.com.tr