

SMART LINE

FACEDE LIGHT

Areas of application

- Shopping Centers
- Stores
- Meeting Halls
- Aisles
- Schools
- Shops
- Offices

Product benefits

- Efficient energy saving
- Elegant design
- Easy installation system

Product Specifications

- Lifetime (L70/B50) : up to 50,000 h
- Color temperature : 2,700 K - 6,500 K
- Operating Voltage : 220...240 V AC supply
- Type of protection : IP67
- Surfaced mounting
- Led Type : Samsung
- Driver : Philips - Meanwell



IP 67



Product datasheet

Technical data

Electrical data

Nominal Wattage	28 W
Nominal Voltage	220 - 240 V
Power Factor	> 0.95
Lumen / Watt	115 lm/watt
Total Harmonic Distortion	< %20
Mains frequency	50...60 Hz

Photometrical data

Color temperature	2700 K - 6500 K
Luminous flux	3224 lm
Color rendering index Ra	> 80

Dimensions

A	172.0 mm
B	72.0 mm
C	72.0 mm

Colors & materials

Body material	Aluminum Extrusion
Product color	Electrostatic Powder Paint

Note : Product body paint can be ordered with other RAL codes.

Temperatures & operating conditions

Ambient temperature range	-25 ... +85 °C
---------------------------	----------------

Light Technical Data

Beam angle	wide distribution - narrow distribution
-------------------	---

Type of cover	PC
----------------------	----

Capabilities

Type of installation	with lighting pole
Type of connection	cable, 3 x 1.50 mm ²

Certificates & standards

Protection class	insulation class I (safety insulation)
Type of protection	IP67